



Association of American Railroads

This table corresponds with AAR Open Top Loading Rules, Section 1, Table 20.2 and Section 7, Table 120.2

Current as of June 10, 2009

AAR Approved Webbing Companies

Company	Ref. Part No.	Type and Width of Webbing	Web MBS	AAR Marking*	Approved Through (mm/yy)
			lb (kg)		
Oppermann Webbing Inc.	P/N 6624051-93	2-in.-wide woven polyester, resin coated.	10,000 (4536)	AAR-76M	06/11
Oppermann Webbing Inc.	P/N 6622051-94	2-in.-wide woven polyester, resin coated.	12,000 (5443)	AAR-76M	06/11
Oppermann Webbing Inc.	P/N 6624076-93	3-in.-wide woven polyester, resin coated.	15,000 (6804)	AAR-76M	06/11
Oppermann Webbing Inc.	P/N 6622076-94	3-in.-wide woven polyester, resin coated.	18,000 (8165)	AAR-76M	06/11
Oppermann Webbing Inc.	P/N 6624102-93	4-in.-wide woven polyester, resin coated.	20,000 (9072)	AAR-76M	06/11
Oppermann Webbing Inc.	P/N 6622102-94	4-in.-wide woven polyester, resin coated.	24,000 (10886)	AAR-76M	06/11
Spanset, Inc.	P/N 141534	LoadGard(tm) woven polyester, uncoated, 4.0 in.	20000 (9092)	AAR-72MA	09/10
Southern Weaving Co.	P/N 1257PL0200	2-in.-wide woven yellow dyed 40148 polyester.	12,000 (5443)	AAR-73M	10/11
Southern Weaving Co.	P/N 1257PL0300	3-in.-wide woven yellow dyed 40148 polyester.	18,000 (8165)	AAR-73M	10/11
Southern Weaving Co.	P/N 1257PL0400	4-in.-wide woven yellow dyed 40148 polyester.	24,000 (10886)	AAR-73M	10/11
Southern Weaving Co.	P/N 1257XP0300	3-in.-wide woven yellow dyed 40148 polyester.	15,000 (6804)	AAR-73M	10/11
American Webbing Inc.	P/N 05004TPT	4-in.-wide woven yellow dyed polyester.	20,000 (9072)	AAR-77M	06/12

* **M** = Approved weaver/manufacturer
MA = Approved weaver and assembler