

**AAR Manual of Standards and Recommended Practices
Freight Car Draft Components**

ALPHABETICAL TABLE OF CONTENTS

Subject	Standard	Page
Bushings, Seamless Steel Tube—Coupler Shanks and Yokes	S-100	B[S-100]131
Coupler Carrier Wear Plate	S-269	B[S-269]189
Cushioning Device Inspection	RP-110	B[RP-110]197
Cushioning Devices, Active Draft End	M-921E	B[M-921E]93
Cushioning Devices, Active Draft End of Car	M-921F	B[M-921F]107
Cushioning Devices, End-of-Car	M-921B	B[M-921B]57
Cushioning Devices, End-of-Car—Motor-Vehicle-Carrying	M-921D	B[M-921D]79
Cushioning Devices, Reconditioned—Approved for Freight Service	M-921C	B[M-921C]73
Cushioning Devices, Sliding Sill	M-921A	B[M-921A]51
Cushioning Pocket Identification Guide—AAR Rule 59	S-181	B[S-181]165
Cushioning Units, Standard Preload EOC Unit Condition Indicator	M-921H	B[M-921H]129
Draft Gear Follower, Y44A	S-119	B[S-119]135
Draft Gear Inspection	RP-101	B[RP-101]193
Draft Gear Reaction Forces, Measuring and Recording, Instrumentation Requirements	M-901F	B[M-901F]33
Draft Gear, All-Hydraulic, Rated by Impact Testing	M-901K	B[M-901K]43
Draft Gear, Rated by Impact Testing	M-901G	B[M-901G]35
Draft Gear, Secondhand and Reconditioned	M-901B	B[M-901B]9
Draft Gears with a Minimum Capacity of 36,000 ft·lb at a Reaction of 500,000 lb	M-901E	B[M-901E]23
Draft Key	S-121	B[S-121]139
Draft Key Retainers, Locks, Keepers, and Washer	S-120	B[S-120]137
Facility Inspection Requirements for Manufacturers of New and Reconditioned Cushioning Devices for Freight Service	M-921G	B[M-921G]121
Field Service Experience—Reporting Requirements	S-101	B[S-101]133
Immobilization of Freightmaster	S-158	B[S-158]153
Immobilization of Freightmaster 10-in. Type E Miner M-12S	S-161	B[S-161]159
Immobilization of Freightmaster Types F, FS, and B	S-157	B[S-157]151
Immobilization of Freightmaster Types HD and AR-F	S-159	B[S-159]155
Immobilization of Freightmaster Types SP-E and SP-C	S-156	B[S-156]149
Immobilization of Keystone F Shank	S-162	B[S-162]161
Immobilization of Keystone Type E Miner SR-12	S-160	B[S-160]157
Immobilization of Pullman Standard, ACF, or Keystone Center-of-Car Cushioning Devices (“Dummy Cylinder Method”)	S-171	B[S-171]163
Immobilization of Sliding Sill on Cushion Underframe Cars Having Damaged or Defective ACF Freight Saver 20- or 30-in. Travel Units—Plate No. 526-1	S-125	B[S-125]141
Immobilization of Sliding Sill on Cushion Underframe Cars Having Damaged or Defective Hydra Cushion 10-, 12-, or 20-in. Travel Units or Evans Cushion Pak Wide Tunnel Units—Plate No. 526-3	S-127	B[S-127]145

IMPLEMENTED 11/01/2012

**AAR Manual of Standards and Recommended Practices
Freight Car Draft Components**

Subject	Standard	Page
Immobilization of Sliding Sill on Cushion Underframe Cars Having Damaged or Defective Hydra Pullman Standard Hydroframe 40 and 60 Units or National 3C Wide Tunnel Units—Plate No. 526-4	S-128	B[S-128]147
Immobilization of Sliding Sill on Cushion Underframe Cars Having Damaged or Defective Keystone 20-in. Travel Unit, Santa Fe Shock Control, A.O. Smith Cushion Ride, and Rockwell Cargo Cushion—Plate No. 526-2	S-126	B[S-126]143
Pin, Coupler Knuckle Pivot and Coupler Shank Connecting, Steel	M-118	B[M-118]1
Pocket Tolerances—EOC-10	S-184	B[S-184]187
Pocket Tolerances—EOC-8	S-182	B[S-182]183
Pocket Tolerances—EOC-9	S-183	B[S-183]185
Retaining Pin and Keeper for F-Type Cushion Yoke with Two-Flange Trainline Support Bracket	M-119	B[M-119]5
Wear Plate, Coupler Carrier, Performance Specification—Non Metallic	M-269	B[M-269]7
Wear Plate, Used in Cushion Unit and Draft Systems that Employ the Y-47 Pin for an F Shank	S-270	B[S-270]191

IMPLEMENTED 11/01/2012

**AAR Manual of Standards and Recommended Practices
Freight Car Draft Components**

NUMERICAL TABLE OF CONTENTS

Standard	Subject	Page
M-118	Pin, Coupler Knuckle Pivot and Coupler Shank Connecting, Steel	B[M-118]1
M-119	Retaining Pin and Keeper for F-Type Cushion Yoke with Two-Flange Trainline Support Bracket	B[M-119]5
M-269	Wear Plate, Coupler Carrier, Performance Specification—Non Metallic	B[M-269]7
M-901B	Draft Gear, Secondhand and Reconditioned	B[M-901B]9
M-901E	Draft Gears with a Minimum Capacity of 36,000 ft·lb at a Reaction of 500,000 lb	B[M-901E]23
M-901F	Draft Gear Reaction Forces, Measuring and Recording, Instrumentation Requirements	B[M-901F]33
M-901G	Draft Gear, Rated by Impact Testing	B[M-901G]35
M-901K	Draft Gear, All-Hydraulic, Rated by Impact Testing	B[M-901K]43
M-921A	Cushioning Devices, Sliding Sill	B[M-921A]51
M-921B	Cushioning Devices, End-of-Car	B[M-921B]57
M-921C	Cushioning Devices, Reconditioned—Approved for Freight Service	B[M-921C]73
M-921D	Cushioning Devices, End-of-Car—Motor-Vehicle-Carrying	B[M-921D]79
M-921E	Cushioning Devices, Active Draft End	B[M-921E]93
M-921F	Cushioning Devices, Active Draft End of Car	B[M-921F]107
M-921G	Facility Inspection Requirements for Manufacturers of New and Reconditioned Cushioning Devices for Freight Service	B[M-921G]121
M-921H	Cushioning Units, Standard Preload EOC Unit Condition Indicator	B[M-921H]129
RP-101	Draft Gear Inspection	B[RP-101]193
RP-110	Cushioning Device Inspection	B[RP-110]197
S-100	Bushings, Seamless Steel Tube—Coupler Shanks and Yokes	B[S-100]131
S-101	Field Service Experience—Reporting Requirements	B[S-101]133
S-119	Draft Gear Follower, Y44A	B[S-119]135
S-120	Draft Key Retainers, Locks, Keepers, and Washer	B[S-120]137
S-121	Draft Key	B[S-121]139
S-125	Immobilization of Sliding Sill on Cushion Underframe Cars Having Damaged or Defective ACF Freight Saver 20- or 30-in. Travel Units—Plate No. 526-1	B[S-125]141
S-126	Immobilization of Sliding Sill on Cushion Underframe Cars Having Damaged or Defective Keystone 20-in. Travel Unit, Santa Fe Shock Control, A.O. Smith Cushion Ride, and Rockwell Cargo Cushion—Plate No. 526-2	B[S-126]143
S-127	Immobilization of Sliding Sill on Cushion Underframe Cars Having Damaged or Defective Hydra Cushion 10-, 12-, or 20-in. Travel Units or Evans Cushion Pak Wide Tunnel Units—Plate No. 526-3	B[S-127]145
S-128	Immobilization of Sliding Sill on Cushion Underframe Cars Having Damaged or Defective Hydra Pullman Standard Hydroframe 40 and 60 Units or National 3C Wide Tunnel Units—Plate No. 526-4	B[S-128]147
S-156	Immobilization of Freightmaster Types SP-E and SP-C	B[S-156]149

IMPLEMENTED 11/01/2012

**AAR Manual of Standards and Recommended Practices
Freight Car Draft Components**

Standard	Subject	Page
S-157	Immobilization of Freightmaster Types F, FS, and B	B[S-157]151
S-158	Immobilization of Freightmaster	B[S-158]153
S-159	Immobilization of Freightmaster Types HD and AR-F	B[S-159]155
S-160	Immobilization of Keystone Type E Miner SR-12	B[S-160]157
S-161	Immobilization of Freightmaster 10-in. Type E Miner M-12S	B[S-161]159
S-162	Immobilization of Keystone F Shank	B[S-162]161
S-171	Immobilization of Pullman Standard, ACF, or Keystone Center-of-Car Cushioning Devices (“Dummy Cylinder Method”)	B[S-171]163
S-181	Cushioning Pocket Identification Guide—AAR Rule 59	B[S-181]165
S-182	Pocket Tolerances—EOC-8	B[S-182]183
S-183	Pocket Tolerances—EOC-9	B[S-183]185
S-184	Pocket Tolerances—EOC-10	B[S-184]187
S-269	Coupler Carrier Wear Plate	B[S-269]189
S-270	Wear Plate, Used in Cushion Unit and Draft Systems that Employ the Y-47 Pin for an F Shank	B[S-270]191

IMPLEMENTED 11/01/2012