

**AAR Manual of Standards and Recommended Practices  
Trucks and Truck Details**

**TABLE OF CONTENTS—ALPHABETICAL**

Subject	Standard	Page
Center Plate Liner Application—220,000-lb GRL	RP-301	D[RP-301]41
Center Plate Liner Application—263,000-lb or Larger	S-308	D[S-308]55
Center Plate Liner—General Application	S-305	D[S-305]49
Center Plate Liner—Horizontal, 263,000-lb GRL and Larger	S-307	D[S-307]53
Center Plate Liner—Performance Requirements	S-3004	D[S-3004]93
Center Plate Liner—Vertical, 220,000-lb GRL	RP-300	D[RP-300]39
Center Plate Liner—Vertical, 263,000-lb GRL and Larger	S-306	D[S-306]51
Freight Car Truck Springs—with Load-Carrying Snubber	S-3014	D[S-3014]115
Freight Car Truck Springs—without Load-Carrying Snubber	S-3015	D[S-3015]119
Hot Bearing Detection—Compatibility Certification for New Truck Designs	S-3007	D[S-3007]97
Peep Hole—Location for Checking Brake Cylinder Piston Travel on Cars with Deep Side Sills	S-373	D[S-373]85
Performance of Devices or Designs to Control Yaw Dynamics in Freight Car Trucks	S-3008	D[S-3008]109
Side Bearing Mounting Pad—Surface Requirements	S-3013	D[S-3013]111
Side Bearing Pad for Two-Hole Application	S-394	D[S-394]89
Side Frame Keys for AAR Standard and Alternate Standard Pedestal-Type Side Frames	S-377	D[S-377]87
Side Frame—Column Friction Wear Plate, Application	S-3003	D[S-3003]91
Side Frame—Column Wear Plate, Application	S-320	D[S-320]57
Snap-On Pedestal Roof Liners for AAR Pedestal-Type Side Frames—Application	RP-323	D[RP-323]47
Spring Test Machine, Electro-Hydraulic	RP-307	D[RP-307]45
Spring Test Machine, Pneumatic	RP-306	D[RP-306]43
Spring—“D” Series, Recertified	S-3006	D[S-3006]95
Spring—D2, 1 5/8-in. Travel	S-332	D[S-332]59
Spring—D3, 2 1/2-in. Travel	S-333	D[S-333]61
Spring—D4, 3 1/16-in. Travel	S-334	D[S-334]63
Spring—D5, 3 11/16-in. Travel	S-335	D[S-335]65
Spring—D6, 3 3/8-in. Travel	S-336	D[S-336]67
Spring—D6A, 3 5/16-in. Travel	S-337	D[S-337]69
Spring—D7, 4 1/4-in. Travel	S-338	D[S-338]71
Spring—Groups for Free, Unrestricted Interchange for 286,000 GRL Cars (M-976 and S-286 Approved Trucks)	S-3016	D[S-3016]121
Spring—Groups without Load-Carrying Snubbers	S-340	D[S-340]75
Spring—Groups with Load-Carrying Snubber (Double-Side Springs)	S-342	D[S-342]79
Spring—Groups with Load-Carrying Snubbers (Single-Side Springs)	S-341	D[S-341]77
Spring—Groups with Hydraulic Snubber	S-343	D[S-343]83
Spring—Groups for D2	S-339	D[S-339]73
Spring—Heat-Treated Steel	M-114	D[M-114]1
Truck Performance for Rail Cars	M-976	D[M-976]31
Truck Side Bearing	M-948	D[M-948]5
Truck Systems to Control Roll Stability of Freight Cars	M-965	D[M-965]25

IMPLEMENTED 09/15/2010

**AAR Manual of Standards and Recommended Practices  
Trucks and Truck Details**

**TABLE OF CONTENTS—NUMERICAL**

<b>Standard</b>	<b>Subject</b>	<b>Page</b>
M-114	Spring—Heat-Treated Steel	D[M-114]1
M-948	Truck Side Bearing	D[M-948]5
M-965	Truck Systems to Control Roll Stability of Freight Cars	D[M-965]25
M-976	Truck Performance for Rail Cars	D[M-976]31
RP-300	Center Plate Liner—Vertical, 220,000-lb GRL	D[RP-300]39
RP-301	Center Plate Liner Application—220,000-lb GRL	D[RP-301]41
RP-306	Spring Test Machine, Pneumatic	D[RP-306]43
RP-307	Spring Test Machine, Electro-Hydraulic	D[RP-307]45
RP-323	Snap-On Pedestal Roof Liners for AAR Pedestal-Type Side Frames—Application	D[RP-323]47
S-305	Center Plate Liner—General Application	D[S-305]49
S-306	Center Plate Liner—Vertical, 263,000-lb GRL and Larger	D[S-306]51
S-307	Center Plate Liner—Horizontal, 263,000-lb GRL and Larger	D[S-307]53
S-308	Center Plate Liner Application—263,000-lb or Larger	D[S-308]55
S-320	Side Frame—Column Wear Plate, Application	D[S-320]57
S-332	Spring—D2, 1 5/8-in. Travel	D[S-332]59
S-333	Spring—D3, 2 1/2-in. Travel	D[S-333]61
S-334	Spring—D4, 3 1/16-in. Travel	D[S-334]63
S-335	Spring—D5, 3 11/16-in. Travel	D[S-335]65
S-336	Spring—D6, 3 3/8-in. Travel	D[S-336]67
S-337	Spring—D6A, 3 5/16-in. Travel	D[S-337]69
S-338	Spring—D7, 4 1/4-in. Travel	D[S-338]71
S-339	Spring—Groups for D2	D[S-339]73
S-340	Spring—Groups without Load-Carrying Snubbers	D[S-340]75
S-341	Spring—Groups with Load-Carrying Snubbers (Single-Side Springs)	D[S-341]77
S-342	Spring—Groups with Load-Carrying Snubber (Double-Side Springs)	D[S-342]79
S-343	Spring—Groups with Hydraulic Snubber	D[S-343]83
S-373	Peep Hole—Location for Checking Brake Cylinder Piston Travel on Cars with Deep Side Sills	D[S-373]85
S-377	Side Frame Keys for AAR Standard and Alternate Standard Pedestal-Type Side Frames	D[S-377]87
S-394	Side Bearing Pad for Two-Hole Application	D[S-394]89
S-3003	Side Frame—Column Friction Wear Plate, Application	D[S-3003]91
S-3004	Center Plate Liner—Performance Requirements	D[S-3004]93
S-3006	Spring—“D” Series, Recertified	D[S-3006]95
S-3007	Hot Bearing Detection—Compatibility Certification for New Truck Designs	D[S-3007]97
S-3008	Performance of Devices or Designs to Control Yaw Dynamics in Freight Car Trucks	D[S-3008]109
S-3013	Side Bearing Mounting Pad—Surface Requirements	D[S-3013]111
S-3014	Freight Car Truck Springs—with Load-Carrying Snubber	D[S-3014]115
S-3015	Freight Car Truck Springs—without Load-Carrying Snubber	D[S-3015]119
S-3016	Spring—Groups for Free, Unrestricted Interchange for 286,000 GRL Cars (M-976 and S-286 Approved Trucks)	D[S-3016]121

**IMPLEMENTED 09/15/2010**