

**AAR Manual of Standards and Recommended Practices  
Brakes and Brake Equipment**

---

**TABLE OF CONTENTS IN  
ALPHABETICAL SEQUENCE**

Subject	Standard	Page
Air Brake and Signal Hose—Mounting of Coupling and Nipple	S-441	E[S-441]277
Air Brake Pipe and Fittings for Railroad Cars—Welding Procedure	S-402	E[S-402]229
Angle Cock and Air Brake Hose Location on Cars with Excessive Overhang Preventing Compliance with AAR Standards S-424, S-425, and S-426	S-427	E[S-427]255
Angle Cock and Brake Hose Location on Cars with EOCC	S-4021	E[S-4021]597
Angle Cock Location	S-424	E[S-424]249
Angle Cock Location on Cars Arranged for Rotary Dump Service	S-495	E[S-495]509
Angle Cock Location on Cars Equipped with AAR Type F Coupler	S-425	E[S-425]251
Angle Cock Location on Cars Equipped with AAR Type F Coupler and Cushioned Underframe	S-428	E[S-428]257
Angle Cock Location on Cars with Floating Sills	S-426	E[S-426]253
Angle Cock Locking Lugs—Minimum Permissible Engagement	S-429	E[S-429]259
Angle Cock, Ball Type—Specification for Approval	S-470	E[S-470]409
Angle Cocks and Brake Pipe End Cocks—Repair Specification	S-476	E[S-476]457
Automated Single-Car Test Procedure, Conventional Brake Equipment—Design and Performance Requirements	S-4027	E[S-4027]1
Badge Plate for Showing Correct Dimensions for Body and Truck Brake Levers	S-374	E[S-374]167
Brake Beam Gauge Application—Hangerless Type	S-355	E[S-355]141
Brake Beam Gauge Assembly—Hangerless Type	S-352	E[S-352]133
Brake Beam Gauge Details—Hangerless Type	S-353	E[S-353]135
Brake Beam Gauges for Standard Brake Beams	S-348	E[S-348]121
Brake Beam Hangers	S-368	E[S-368]157
Brake Beam Hangers and Attachments	S-369	E[S-369]159
Brake Beam Safety Supports—AAR Approval Procedure	S-3001	E[S-3001]513
Brake Beam Specifications and Tests	S-344	E[S-344]109
Brake Beam Strut Keyway Gauge	RP-322	E[RP-322]37
Brake Beam Tolerance, Hangerless Type	S-345	E[S-345]117
Brake Beam Wear Liners, Non-Metallic	S-4025	E[S-4025]609
Brake Beam, Reconditioned	M-300	E[M-300]1
Brake Beam—Outline, Hanger Type	S-346	E[S-346]119
Brake Beam—Outline, Hangerless Type	S-349	E[S-349]131
Brake Beam—Universal Brake Beam Gauge	S-3005	E[S-3005]515
Brake Bottom Rod Safety Supports	S-399	E[S-399]177
Brake Cylinder Line Hose Assemblies—Performance Requirements	M-619	E[M-619]33
Brake Cylinder Lubricant	M-914	E[M-914]47
Brake Cylinder Pressure Measurement Taps	S-4020	E[S-4020]593
Brake Cylinder Release Valve and Release Rod	S-443	E[S-443]279
Brake Cylinder Release Valve Rod Handles—Location	S-444	E[S-444]283

IMPLEMENTED 02/25/2010

**AAR Manual of Standards and Recommended Practices  
Brakes and Brake Equipment**

Subject	Standard	Page
Brake Cylinder—Performance Testing	S-4004	E[S-4004]559
Brake Design Requirements	S-401	E[S-401]217
Brake Equipment—Application Form for AAR Approval of New and Untried Freight Cars	S-473	E[S-473]423
Brake Equipment—Installation Specifications	S-400	E[S-400]179
Brake Hanger Bracket—Design Dimensions	RP-308	E[RP-308]35
Brake Hanger Brackets and Unit Guide Brackets—Standard Location	S-365	E[S-365]153
Brake Head Conversion—Metal Shoe-Type to High-Friction Composition	S-372	E[S-372]165
Brake Head—Limiting Contour of Brake Head Face for Hangerless-Type Brake Beams	S-371	E[S-371]163
Brake Head—Limiting Contour of Brake Head Face for Hanger-Type Brake Beams	S-370	E[S-370]161
Brake Pipe Reduction Devices, Freight Auxiliary—Environmental Tests	S-4000	E[S-4000]527
Brake Pipe Restriction Test	S-471	E[S-471]415
Brake Rod Connector—Design Requirements	S-4026	E[S-4026]611
Brake Shoe Force Measurement Devices—Performance Specification	S-4024	E[S-4024]605
Brake Shoe Go Gauge	S-448	E[S-448]293
Brake Shoe Keys	S-376	E[S-376]171
Brake Shoe Limiting Contour, Low-Friction Composition Type	S-4023	E[S-4023]603
Brake Shoe No-Go Gauge	S-449	E[S-449]295
Brake Shoe, Cast Iron, High-Phosphorus Type	M-402	E[M-402]7
Brake Shoe, High-Friction Composition or Metal Type	M-926	E[M-926]57
Brake Shoe, High-Friction Composition Type—Limiting Contour	S-431	E[S-431]263
Brake Shoe, High-Friction Tread Conditioning—High Capacity	M-997	E[M-997]97
Brake Shoe, Low-Friction Composition Type	M-996	E[M-996]89
Brake Shoe, Metal, Reinforced	S-430	E[S-430]261
Brake Systems, Truck-Mounted—Performance Testing	S-4005	E[S-4005]563
Brake Pin Tolerance	S-375	E[S-375]169
Code of Air Brake System Tests for Freight Equipment—Single Car Test	S-486	E[S-486]461
Compression Slack Adjusters—Inspection, Testing, Removal, and Application	S-4009	E[S-4009]581
Control Valve Pipe Bracket	S-468	E[S-468]399
Control Valve, Freight Brake—Environmental Tests	S-467	E[S-467]395
Control Valve—Approval Procedure	S-462	E[S-462]323
Control Valve—Shop Certification Requirements for Approved Valves	S-477	E[S-477]459
Cotter Keys, Self-Locking	S-3009	E[S-3009]525
Dirt Collector and Cutout Cock, Combined—Repair Specification	S-489	E[S-489]485
Dirt Collector and Cutout Cock—Test Specification	S-493	E[S-493]497
Empty/Load Devices—Performance Testing	S-4002	E[S-4002]537

IMPLEMENTED 02.25/2010

**AAR Manual of Standards and Recommended Practices  
Brakes and Brake Equipment**

---

Subject	Standard	Page
End Cock and Air Brake Hose Location on Long Cars	S-488	E[S-488]483
End Cock Location on Cars Arranged for Rotary Dump Service	S-472	E[S-472]421
End Hose Gaskets, Couplings, and Nipples—Annual Test Requirements	S-440	E[S-440]275
Field Service Reports—Requirements	S-492	E[S-492]495
Freight Brakes—Performance Specification	S-469	E[S-469]405
Gaskets, Air Hose	M-602	E[M-602]21
Gauge, End of Hangerless-Type Brake Beam	S-360	E[S-360]147
Gauges, Go and No-Go—for Brake Head, Limiting Contour of Face, Metal or High-Friction Shoe	S-359	E[S-359]145
Gauges, Go Gauge—for Brake Head, Metal or High-Friction Shoe	S-358	E[S-358]143
Gauges, Go Gauge—for Brake Shoe	S-361	E[S-361]149
Gauges, No-Go Gauge—for Brake Shoe	S-362	E[S-362]151
Hand Brakes	S-475	E[S-475]425
Hangerless Brake Beam Extension Functional Gauge (Parallelism)	S-380	E[S-380]175
Hanger-Type Brake Beams—Application Tolerance	S-379	E[S-379]173
Hook and Eye Brake Rigging—Lever Angularity Inspection	RP-5599	E[RP-5599]41
Hose Assemblies—Reclamation Procedures	S-458	E[S-458]315
Hose Cement	M-923	E[M-923]55
Hose Clamps	S-439	E[S-439]273
Hose Coupling	S-491	E[S-491]489
Hose Coupling Condemning Gauges for Checking the Beads and Shanks on New and Used Hose Couplings and Nipples	S-455	E[S-455]297
Hose Coupling Gasket Gauge	S-447	E[S-447]291
Hose Coupling Gauges for Gauging New and Used Couplings	S-456	E[S-456]299
Hose Coupling Tester, Air Brake, Type A-1-B—Modification to Permit Testing of Pinless-Type Couplings	S-457	E[S-457]313
Hose Coupling, Dummy	S-436	E[S-436]267
Hose Fittings and Hose Assemblies, Air, Wire-Reinforced	M-927	E[M-927]67
Hose Support, S Hook	S-432	E[S-432]265
Hose Supports—Performance Testing	S-4006	E[S-4006]567
Hose, Air, Fabric-Reinforced	M-620	E[M-620]39
Hose, Air, Wire-Reinforced	M-618	E[M-618]27
Hose, Armored Type—Mounting Procedure	S-438	E[S-438]271
Hose, Other than Armored Type—Mounting Procedure	S-437	E[S-437]269
Hose, Wrapped, Air—Brake, “End Hose”	M-601	E[M-601]15
Oil, Control Valve	M-912	E[M-912]45
Pipe, Other than Schedule 80 Iron	S-4022	E[S-4022]601
Push Rod, Brake Cylinder	S-2009	E[S-2009]511
Reservoir, Combined Auxiliary and Emergency—Reclamation Procedure	S-4007	E[S-4007]571
Reservoir, Steel Fabricated, Combined Auxiliary and Emergency	S-494	E[S-494]501

IMPLEMENTED 02/25/2010

**AAR Manual of Standards and Recommended Practices  
Brakes and Brake Equipment**

---

Subject	Standard	Page
Retaining Valve, 1967-Type, Three-Position	S-446	E[S-446]289
Retaining Valve—Location	S-445	E[S-445]285
Rubber Products—Performance Testing	S-4001	E[S-4001]531
Single-Capacity Freight Brakes—Performance Specification	S-461	E[S-461]319
Slack Adjuster Grease	M-949	E[M-949]85
Slack Adjuster Reclamation—Automatic, Double-Acting, Mechanical Slack Adjusters	S-423	E[S-423]245
Slack Adjuster, Center Rod Application (Group E)	S-421	E[S-421]241
Slack Adjuster, Mechanical, Double-Acting, Automatic Compression	S-4008	E[S-4008]573
Slack Adjuster, Mechanical, Double-Acting, Automatic Tension	S-419	E[S-419]231
Slack Adjuster, Tension—Inspection, Testing, Removal, and Application	S-4010	E[S-4010]587
Slack Adjuster, Tension—Limiting Design Dimensions	S-420A	E[S-420A]239
Slack Adjuster, Top Rod Application (Group E)	S-422	E[S-422]243
Slack Adjuster—General Information	RP-400	E[RP-400]39
Slack Adjuster—Limiting Design Dimensions (Group E)	S-420	E[S-420]237
Test Rack, 150-Car, Freight Brake	S-463	E[S-463]327
Test Rack, 150-Car—Performance Testing Procedure	S-464	E[S-464]333
Test Rack, Single-Car	S-465	E[S-465]383
Test Rack, Single-Car, for Individual Valve Portions—Performance Testing Procedure	S-466	E[S-466]387
Train Line Arrangement for Cars with F-Shank Couplers	S-4003	E[S-4003]553
Train Line Arrangement with Displaceable Union on Cars with EOCC and Couplers Exceeding 45 in. in Length	S-4029	E[S-4029]27
Train Line Arrangement with Displaceable Union on Cars with EOCC and Couplers Not Exceeding 45 in. in Length	S-4028	E[S-4028]23
Train Line Hoses—Coupling Extension Adapter	S-4013	E[S-4013]591
Trolley Arrangement on Cars with EOCC and E-Shank Couplers	S-4030	E[S-4030]31
Vent Protector Performance and Approval	S-490	E[S-490]487
Wear Plate for Unit-Type Brake Beam Guide in Side Frame	S-367	E[S-367]155

IMPLEMENTED 02.25/2010

**AAR Manual of Standards and Recommended Practices  
Brakes and Brake Equipment**

---

**TABLE OF CONTENTS IN  
NUMERICAL SEQUENCE**

<b>Standard</b>	<b>Subject</b>	<b>Page</b>
M-300	Brake Beam, Reconditioned	E[M-300]1
M-402	Brake Shoe, Cast Iron, High-Phosphorus Type	E[M-402]7
M-601	Hose, Wrapped, Air—Brake, “End Hose”	E[M-601]15
M-602	Gaskets, Air Hose	E[M-602]21
M-618	Hose, Air, Wire-Reinforced	E[M-618]27
M-619	Brake Cylinder Line Hose Assemblies—Performance Requirements	E[M-619]33
M-620	Hose, Air, Fabric-Reinforced	E[M-620]39
M-912	Oil, Control Valve	E[M-912]45
M-914	Brake Cylinder Lubricant	E[M-914]47
M-923	Hose Cement	E[M-923]55
M-926	Brake Shoe, High-Friction Composition or Metal Type	E[M-926]57
M-927	Hose Fittings and Hose Assemblies, Air, Wire-Reinforced	E[M-927]67
M-949	Slack Adjuster Grease	E[M-949]85
M-996	Brake Shoe, Low-Friction Composition Type	E[M-996]89
M-997	Brake Shoe, High-Friction Tread Conditioning—High Capacity	E[M-997]97
RP-308	Brake Hanger Bracket—Design Dimensions	E[RP-308]35
RP-322	Brake Beam Strut Keyway Gauge	E[RP-322]37
RP-400	Slack Adjuster—General Information	E[RP-400]39
RP-5599	Hook and Eye Brake Rigging—Lever Angularity Inspection	E[RP-5599]41
S-344	Brake Beam Specifications and Tests	E[S-344]109
S-345	Brake Beam Tolerance, Hangerless Type	E[S-345]117
S-346	Brake Beam—Outline, Hanger Type	E[S-346]119
S-348	Brake Beam Gauges for Standard Brake Beams	E[S-348]121
S-349	Brake Beam—Outline, Hangerless Type	E[S-349]131
S-352	Brake Beam Gauge Assembly—Hangerless Type	E[S-352]133
S-353	Brake Beam Gauge Details—Hangerless Type	E[S-353]135
S-355	Brake Beam Gauge Application—Hangerless Type	E[S-355]141
S-358	Gauges, Go Gauge—for Brake Head, Metal or High-Friction Shoe	E[S-358]143
S-359	Gauges, Go and No-Go—for Brake Head, Limiting Contour of Face, Metal or High-Friction Shoe	E[S-359]145
S-360	Gauge, End of Hangerless-Type Brake Beam	E[S-360]147
S-361	Gauges, Go Gauge—for Brake Shoe	E[S-361]149
S-362	Gauges, No-Go Gauge—for Brake Shoe	E[S-362]151
S-365	Brake Hanger Brackets and Unit Guide Brackets—Standard Location	E[S-365]153
S-367	Wear Plate for Unit-Type Brake Beam Guide in Side Frame	E[S-367]155
S-368	Brake Beam Hangers	E[S-368]157
S-369	Brake Beam Hangers and Attachments	E[S-369]159

IMPLEMENTED 02/25/2010

**AAR Manual of Standards and Recommended Practices  
Brakes and Brake Equipment**

**IMPLEMENTED 02.25/2010**

<b>Standard</b>	<b>Subject</b>	<b>Page</b>
S-370	Brake Head—Limiting Contour of Brake Head Face for Hanger-Type Brake Beams	E[S-370]161
S-371	Brake Head—Limiting Contour of Brake Head Face for Hangerless-Type Brake Beams	E[S-371]163
S-372	Brake Head Conversion—Metal Shoe-Type to High-Friction Composition	E[S-372]165
S-374	Badge Plate for Showing Correct Dimensions for Body and Truck Brake Levers	E[S-374]167
S-375	Brake Pin Tolerance	E[S-375]169
S-376	Brake Shoe Keys	E[S-376]171
S-379	Hanger-Type Brake Beams—Application Tolerance	E[S-379]173
S-380	Hangerless Brake Beam Extension Functional Gauge (Parallelism)	E[S-380]175
S-399	Brake Bottom Rod Safety Supports	E[S-399]177
S-400	Brake Equipment—Installation Specifications	E[S-400]179
S-401	Brake Design Requirements	E[S-401]217
S-402	Air Brake Pipe and Fittings for Railroad Cars—Welding Procedure	E[S-402]229
S-419	Slack Adjuster, Mechanical, Double-Acting, Automatic Tension	E[S-419]231
S-420	Slack Adjuster—Limiting Design Dimensions (Group E)	E[S-420]237
S-420A	Slack Adjuster, Tension—Limiting Design Dimensions	E[S-420A]239
S-421	Slack Adjuster, Center Rod Application (Group E)	E[S-421]241
S-422	Slack Adjuster, Top Rod Application (Group E)	E[S-422]243
S-423	Slack Adjuster Reclamation—Automatic, Double-Acting, Mechanical Slack Adjusters	E[S-423]245
S-424	Angle Cock Location	E[S-424]249
S-425	Angle Cock Location on Cars Equipped with AAR Type F Coupler	E[S-425]251
S-426	Angle Cock Location on Cars with Floating Sills	E[S-426]253
S-427	Angle Cock and Air Brake Hose Location on Cars with Excessive Overhang Preventing Compliance with AAR Standards S-424, S-425, and S-426	E[S-427]255
S-428	Angle Cock Location on Cars Equipped with AAR Type F Coupler and Cushioned Underframe	E[S-428]257
S-429	Angle Cock Locking Lugs—Minimum Permissible Engagement	E[S-429]259
S-430	Brake Shoe, Metal, Reinforced	E[S-430]261
S-431	Brake Shoe, High-Friction Composition Type—Limiting Contour	E[S-431]263
S-432	Hose Support, S Hook	E[S-432]265
S-436	Hose Coupling, Dummy	E[S-436]267
S-437	Hose, Other than Armored Type—Mounting Procedure	E[S-437]269
S-438	Hose, Armored Type—Mounting Procedure	E[S-438]271
S-439	Hose Clamps	E[S-439]273
S-440	End Hose Gaskets, Couplings, and Nipples—Annual Test Requirements	E[S-440]275
S-441	Air Brake and Signal Hose—Mounting of Coupling and Nipple	E[S-441]277
S-443	Brake Cylinder Release Valve and Release Rod	E[S-443]279

**AAR Manual of Standards and Recommended Practices  
Brakes and Brake Equipment**

---

IMPLEMENTED 02/25/2010

<b>Standard</b>	<b>Subject</b>	<b>Page</b>
S-444	Brake Cylinder Release Valve Rod Handles—Location	E[S-444]283
S-445	Retaining Valve—Location	E[S-445]285
S-446	Retaining Valve, 1967-Type, Three-Position	E[S-446]289
S-447	Hose Coupling Gasket Gauge	E[S-447]291
S-448	Brake Shoe Go Gauge	E[S-448]293
S-449	Brake Shoe No-Go Gauge	E[S-449]295
S-455	Hose Coupling Condemning Gauges for Checking the Beads and Shanks on New and Used Hose Couplings and Nipples	E[S-455]297
S-456	Hose Coupling Gauges for Gauging New and Used Couplings	E[S-456]299
S-457	Hose Coupling Tester, Air Brake, Type A-1-B—Modification to Permit Testing of Pinless-Type Couplings	E[S-457]313
S-458	Hose Assemblies—Reclamation Procedures	E[S-458]315
S-461	Single-Capacity Freight Brakes—Performance Specification	E[S-461]319
S-462	Control Valve—Approval Procedure	E[S-462]323
S-463	Test Rack, 150-Car, Freight Brake	E[S-463]327
S-464	Test Rack, 150-Car—Performance Testing Procedure	E[S-464]333
S-465	Test Rack, Single-Car	E[S-465]383
S-466	Test Rack, Single-Car, for Individual Valve Portions—Performance Testing Procedure	E[S-466]387
S-467	Control Valve, Freight Brake—Environmental Tests	E[S-467]395
S-468	Control Valve Pipe Bracket	E[S-468]399
S-469	Freight Brakes—Performance Specification	E[S-469]405
S-470	Angle Cock, Ball Type—Specification for Approval	E[S-470]409
S-471	Brake Pipe Restriction Test	E[S-471]415
S-472	End Cock Location on Cars Arranged for Rotary Dump Service	E[S-472]421
S-473	Brake Equipment—Application Form for AAR Approval of New and Untried Freight Cars	E[S-473]423
S-475	Hand Brakes	E[S-475]425
S-476	Angle Cocks and Brake Pipe End Cocks—Repair Specification	E[S-476]457
S-477	Control Valve—Shop Certification Requirements for Approved Valves	E[S-477]459
S-486	Code of Air Brake System Tests for Freight Equipment—Single Car Test	E[S-486]461
S-488	End Cock and Air Brake Hose Location on Long Cars	E[S-488]483
S-489	Dirt Collector and Cutout Cock, Combined—Repair Specification	E[S-489]485
S-490	Vent Protector Performance and Approval	E[S-490]487
S-491	Hose Coupling	E[S-491]489
S-492	Field Service Reports—Requirements	E[S-492]495
S-493	Dirt Collector and Cutout Cock—Test Specification	E[S-493]497
S-494	Reservoir, Steel Fabricated, Combined Auxiliary and Emergency	E[S-494]501
S-495	Angle Cock Location on Cars Arranged for Rotary Dump Service	E[S-495]509
S-2009	Push Rod, Brake Cylinder	E[S-2009]511
S-3001	Brake Beam Safety Supports—AAR Approval Procedure	E[S-3001]513

**AAR Manual of Standards and Recommended Practices  
Brakes and Brake Equipment**

---

<b>Standard</b>	<b>Subject</b>	<b>Page</b>
S-3005	Brake Beam—Universal Brake Beam Gauge	E[S-3005]515
S-3009	Cotter Keys, Self-Locking	E[S-3009]525
S-4000	Brake Pipe Reduction Devices, Freight Auxiliary—Environmental Tests	E[S-4000]527
S-4001	Rubber Products—Performance Testing	E[S-4001]531
S-4002	Empty/Load Devices—Performance Testing	E[S-4002]537
S-4003	Train Line Arrangement for Cars with F-Shank Couplers	E[S-4003]553
S-4004	Brake Cylinder—Performance Testing	E[S-4004]559
S-4005	Brake Systems, Truck-Mounted—Performance Testing	E[S-4005]563
S-4006	Hose Supports—Performance Testing	E[S-4006]567
S-4007	Reservoir, Combined Auxiliary and Emergency—Reclamation Procedure	E[S-4007]571
S-4008	Slack Adjuster, Mechanical, Double-Acting, Automatic Compression	E[S-4008]573
S-4009	Compression Slack Adjusters—Inspection, Testing, Removal, and Application	E[S-4009]581
S-4010	Slack Adjuster, Tension—Inspection, Testing, Removal, and Application	E[S-4010]587
S-4013	Train Line Hoses—Coupling Extension Adapter	E[S-4013]591
S-4020	Brake Cylinder Pressure Measurement Taps	E[S-4020]593
S-4021	Angle Cock and Brake Hose Location on Cars with EOCC	E[S-4021]597
S-4022	Pipe, Other than Schedule 80 Iron	E[S-4022]601
S-4023	Brake Shoe Limiting Contour, Low-Friction Composition Type	E[S-4023]603
S-4024	Brake Shoe Force Measurement Devices—Performance Specification	E[S-4024]605
S-4025	Brake Beam Wear Liners, Non-Metallic	E[S-4025]609
S-4026	Brake Rod Connector—Design Requirements	E[S-4026]611
S-4027	Automated Single-Car Test Procedure, Conventional Brake Equipment—Design and Performance Requirements	E[S-4027]1
S-4028	Train Line Arrangement with Displaceable Union on Cars with EOCC and Couplers Not Exceeding 45 in. in Length	E[S-4028]23
S-4029	Train Line Arrangement with Displaceable Union on Cars with EOCC and Couplers Exceeding 45 in. in Length	E[S-4029]27
S-4030	Trolley Arrangement on Cars with EOCC and E-Shank Couplers	E[S-4030]31

IMPLEMENTED 02.25/2010