

**AAR Manual of Standards and Recommended Practices
Coupler and Yoke Details**

TABLE OF CONTENTS—ALPHABETICAL

| Subject | Standard | Page |
|--|----------|----------------|
| Coupler (Rotary), Type E60, Operating Rod, use with up to 6 1/2-in. Total Draft Gear Travel | S-131 | S-III[S-131]45 |
| Coupler (Rotary), Type F70, Operating Rod, use with up to 6 1/2-in. Total Draft Gear Travel | S-133 | S-III[S-133]49 |
| Coupler (Rotary), Types E60, E67, and F70, Operating Rod for Use with Standard Draft Gear or End-of-Car Cushioning up to 15-in. Total Travel | S-134 | S-III[S-134]51 |
| Coupler Centering Device Specification | M-932 | S-III[M-932]1 |
| Coupler Contour, F Type, Interlocking | S-117 | S-III[S-117]39 |
| Coupler Shank Wear Plates and Application | S-137 | S-III[S-137]53 |
| Coupler, E Type, Articulated Rotor Lever Assembly | S-130 | S-III[S-130]43 |
| Coupler, E Type, Detail Parts | S-105 | S-III[S-105]17 |
| Coupler, E Type, Guard Arm Lightener Hole Openings and Knuckle Flag Hole—Standard Dimensions | S-173 | S-III[S-173]85 |
| Coupler, E Type, No. 10-A Contour and Detail of Pivot Pin Hole | S-106 | S-III[S-106]19 |
| Coupler, E Type, SBE60DE and SBE60EE, Bottom Shelf | S-163 | S-III[S-163]75 |
| Coupler, E Type, SBE67CE and SBE67DE, Bottom Shelf | S-164 | S-III[S-164]77 |
| Coupler, E Type, SE67CE and SE67DE, Top and Bottom Shelf | S-154 | S-III[S-154]71 |
| Coupler, E/F Type, SE68CE and SE68DE, Top and Bottom Shelf | S-155 | S-III[S-155]73 |
| Coupler, E Type, Standard and Alternate Standard, E60DE and E60EE | S-102 | S-III[S-102]13 |
| Coupler, E Type, Standard and Alternate Standard, E67CE and E67DE | S-107 | S-III[S-107]21 |
| Coupler, F Type, Standard F Coupler, F70DE | S-110 | S-III[S-110]27 |
| Coupler, E Type, Top and Bottom Shelf, Standard and Alternate Standard, SE60DE and SE60EE | S-103 | S-III[S-103]15 |
| Coupler, E/F Type, SBE69BE and SBE69CE, Bottom Shelf | S-170 | S-III[S-170]81 |
| Coupler, E/F Type, SE69BE and SE69CE, Top and Bottom Shelf | S-172 | S-III[S-172]83 |
| Coupler, E/F Type, Standard and Alternate Standard, E68CE and E68DE | S-108 | S-III[S-108]23 |
| Coupler, E/F Type, Standard and Alternate Standard, E69BE and E69CE | S-109 | S-III[S-109]25 |
| Coupler, E/F Type, SBE68CE and SBE68DE, Bottom Shelf | S-165 | S-III[S-165]79 |
| Coupler, F Type, Guard Arm Lightener Hole Openings and Knuckle Flag Hole—Standard Dimensions | S-174 | S-III[S-174]87 |
| Coupler, F Type, Interlocking, Coupler and Yoke Parts | S-116 | S-III[S-116]37 |
| Coupler, F Type, Standard, F73BE | S-112 | S-III[S-112]31 |
| Coupler, F Type, Standard, F79DE | S-114 | S-III[S-114]33 |
| Coupler, F Type, with Top Shelf, Standard, SF70DE | S-111 | S-III[S-111]29 |
| Coupler, F Type, with Top Shelf, Standard, SF79DE | S-115 | S-III[S-115]35 |
| Couplers—Arrangement of Operating Mechanisms | S-129 | S-III[S-129]41 |
| Operating Mechanism, Type No. 6, Interlocking | S-132 | S-III[S-132]47 |
| Uncoupling Devices, Special | M-961 | S-III[M-961]5 |

IMPLEMENTED 08/30/2016

**AAR Manual of Standards and Recommended Practices
Coupler and Yoke Details**

| Subject | Standard | Page |
|--|-----------------|----------------|
| Yoke, F Type, Cushioning, for Pocket EOC-1, EOC-2, and EOC-16 | S-180 | S-III[S-180]97 |
| Yoke, F Type, Cushioning, for Pocket EOC-10 and EOC 26 | S-179 | S-III[S-179]95 |
| Yoke, E Type, Cushioning, for Pocket EOC-7 | S-176 | S-III[S-176]89 |
| Yoke, E Type, Cushioning, for Pocket EOC-8 | S-177 | S-III[S-177]91 |
| Yoke, F Type, Cushioning, for Pocket EOC-9 | S-178 | S-III[S-178]93 |
| Yoke, E Type, SY40AE or YS93AE, Standard, for 24 5/8-in. Draft Gear Pocket | S-143 | S-III[S-143]65 |
| Yoke, E Type, Y40AE, Standard, for 24 5/8-in. Draft Gear Pocket | S-141 | S-III[S-141]61 |
| Yoke, E Type, Y41AE for 36-in. Draft Gear Pocket | S-142 | S-III[S-142]63 |
| Yoke, E/F and F Type, Y45AE, Standard, for 24 5/8-in. Draft Gear Pocket | S-149 | S-III[S-149]67 |
| Yoke, E/F Type, Y49AE, Standard, for 36-in. Draft Gear Pocket | S-151 | S-III[S-151]69 |
| Yokes, Relief Fillets | S-139 | S-III[S-139]59 |

IMPLEMENTED 08/30/2016

**AAR Manual of Standards and Recommended Practices
Coupler and Yoke Details**

TABLE OF CONTENTS—NUMERICAL

| Standard | Subject | Page |
|-----------------|--|----------------|
| M-932 | Coupler Centering Device Specification | S-III[M-932]1 |
| M-961 | Uncoupling Devices, Special | S-III[M-961]5 |
| S-102 | Coupler, E Type, Standard and Alternate Standard, E60DE and E60EE | S-III[S-102]13 |
| S-103 | Coupler, E Type, Top and Bottom Shelf, Standard and Alternate Standard, SE60DE and SE60EE | S-III[S-103]15 |
| S-105 | Coupler, E Type, Detail Parts | S-III[S-105]17 |
| S-106 | Coupler, E Type, No. 10-A Contour and Detail of Pivot Pin Hole | S-III[S-106]19 |
| S-107 | Coupler, E Type, Standard and Alternate Standard, E67CE and E67DE | S-III[S-107]21 |
| S-108 | Coupler, E/F Type, Standard and Alternate Standard, E68CE and E68DE | S-III[S-108]23 |
| S-109 | Coupler, E/F Type, Standard and Alternate Standard, E69BE and E69CE | S-III[S-109]25 |
| S-110 | Coupler, F Type, Standard F Coupler, F70DE | S-III[S-110]27 |
| S-111 | Coupler, F Type, with Top Shelf, Standard, SF70DE | S-III[S-111]29 |
| S-112 | Coupler, F Type, Standard, F73BE | S-III[S-112]31 |
| S-114 | Coupler, F Type, Standard, F79DE | S-III[S-114]33 |
| S-115 | Coupler, F Type, with Top Shelf, Standard, SF79DE | S-III[S-115]35 |
| S-116 | Coupler, F Type, Interlocking, Coupler and Yoke Parts | S-III[S-116]37 |
| S-117 | Coupler Contour, F Type, Interlocking | S-III[S-117]39 |
| S-129 | Couplers—Arrangement of Operating Mechanisms | S-III[S-129]41 |
| S-130 | Coupler, E Type, Articulated Rotor Lever Assembly | S-III[S-130]43 |
| S-131 | Coupler (Rotary), Type E60, Operating Rod, use with up to 6 1/2-in. Total Draft Gear Travel | S-III[S-131]45 |
| S-132 | Operating Mechanism, Type No. 6, Interlocking | S-III[S-132]47 |
| S-133 | Coupler (Rotary), Type F70, Operating Rod, use with up to 6 1/2-in. Total Draft Gear Travel | S-III[S-133]49 |
| S-134 | Coupler (Rotary), Types E60, E67, and F70, Operating Rod for Use with Standard Draft Gear or End-of-Car Cushioning up to 15-in. Total Travel | S-III[S-134]51 |
| S-137 | Coupler Shank Wear Plates and Application | S-III[S-137]53 |
| S-139 | Yokes, Relief Fillets | S-III[S-139]59 |
| S-141 | Yoke, E Type, Y40AE, Standard, for 24 5/8-in. Draft Gear Pocket | S-III[S-141]61 |
| S-142 | Yoke, E Type, Y41AE for 36-in. Draft Gear Pocket | S-III[S-142]63 |
| S-143 | Yoke, E Type, SY40AE or YS93AE, Standard, for 24 5/8-in. Draft Gear Pocket | S-III[S-143]65 |
| S-149 | Yoke, E/F and F Type, Y45AE, Standard, for 24 5/8-in. Draft Gear Pocket | S-III[S-149]67 |
| S-151 | Yoke, E/F Type, Y49AE, Standard, for 36-in. Draft Gear Pocket | S-III[S-151]69 |
| S-154 | Coupler, E Type, SE67CE and SE67DE, Top and Bottom Shelf | S-III[S-154]71 |
| S-155 | Coupler, E/F Type, SE68CE and SE68DE, Top and Bottom Shelf | S-III[S-155]73 |
| S-163 | Coupler, E Type, SBE60DE and SBE60EE, Bottom Shelf | S-III[S-163]75 |
| S-164 | Coupler, E Type, SBE67CE and SBE67DE, Bottom Shelf | S-III[S-164]77 |

IMPLEMENTED 08/30/2016

AAR Manual of Standards and Recommended Practices
Coupler and Yoke Details

| Standard | Subject | Page |
|-----------------|--|----------------|
| S-165 | Coupler, E/F Type, SBE68CE and SBE68DE, Bottom Shelf | S-III[S-165]79 |
| S-170 | Coupler, E/F Type, SBE69BE and SBE69CE, Bottom Shelf | S-III[S-170]81 |
| S-172 | Coupler, E/F Type, SE69BE and SE69CE, Top and Bottom Shelf | S-III[S-172]83 |
| S-173 | Coupler, E Type, Guard Arm Lightener Hole Openings and Knuckle Flag Hole—Standard Dimensions | S-III[S-173]85 |
| S-174 | Coupler, F Type, Guard Arm Lightener Hole Openings and Knuckle Flag Hole—Standard Dimensions | S-III[S-174]87 |
| S-176 | Yoke, E Type, Cushioning, for Pocket EOC-7 | S-III[S-176]89 |
| S-177 | Yoke, E Type, Cushioning, for Pocket EOC-8 | S-III[S-177]91 |
| S-178 | Yoke, F Type, Cushioning, for Pocket EOC-9 | S-III[S-178]93 |
| S-179 | Yoke, F Type, Cushioning, for Pocket EOC-10 and EOC 26 | S-III[S-179]95 |
| S-180 | Yoke, F Type, Cushioning, for Pocket EOC-1, EOC-2, and EOC-16 | S-III[S-180]97 |

IMPLEMENTED 08/30/2016