

Chock Restraints Only - All Models
Auto Trans in Park unless noted below; Manual Trans in Neutral
Parking Brake Applied
3" Minimum Roof Clearance is Standard at A1 and A5 unless noted below

NISSAN MODELS	3mph MAX speed over bridge plates on Deck A	4 Degrees or less bridge plate angle	2.5" Min Roof Clearance OK on A1 or A5	Deck /Railcar Restrictions	Side Mirror Restrictions	Other Special Handling
ALTIMA SEDAN	x	x	x			Close clearance splashguard to chock and rail, Install chock from inside
ARMADA				Double Chock Front Tires at A1,A5, B1, B5	Use Power Switch to Fold	IEC Holden Grate Lock Chock in Max high position
FRONTIER						
GTR	Creep Speed loading and unloading			No A Deck Use 2" Risers		
GTR NISMO						
JUKE				No A or B deck on Tri-level No Rave Door Tri-Level Loading		
LEAF				No A or B deck on Tri-level No Rave Door Tri-Level Loading		2" Risers on Front wheels w/splashguards
MAXIMA **New Model Changes**	x			No Load in A5 very low chock to splash guard clearance		Auto Trans in Park - NEW Model
MURANO						Auto Trans in Park - NEW Model
MURANO CONVERTIBLE						Auto Trans in Neutral
NV200 and TAXI						
NV Standard and BUS Roof				NV Standard B Deck Only		Double Chock Front Tires at A1 ,A5, B1, B5
NV HIGH Roof				B Deck Automax Railcar Only		
PATHFINDER						IEC Holden Grate Lock Chock in Max high position
QUEST				Bi-Level ONLY Double Chock Front Tires at A1 ,A5, B1, B5		Auto Trans in Neutral No splash guards - Chock in High Splash guard Front - Chock in Low Splash guards Rear - Chock in Medium
ROGUE						Grate Lock Chock low level on front wheel and level 2 on rear wheel.

Chock Restraints Only - All Models
Auto Trans in Park unless noted below; Manual Trans in Neutral
Parking Brake Applied
3" Minimum Roof Clearance is Standard at A1 and A5 unless noted below

NISSAN MODELS	3mph MAX speed over bridge plates on Deck A	4 Degrees or less bridge plate angle	2.5" Min Roof Clearance OK on A1 or A5	Deck /Railcar Restrictions	Side Mirror Restrictions	Other Special Handling
SENTRA			x			
TITAN *Includes New Model Changes*						IEC Holden Grate Lock Chock in Max high position
VERSA						
VERSA Hatchback						
XTERRA						IEC Holden Grate Lock Chock in Max high position
370Z COUPE	No A deck on Tri-level					CAUTION: Install/remove chock between splashguard and tire
370Z CONVERTIBLE	Loading ramps Must Only be on deck and no chock rails Inboard side rails on loading ramp 1" MAX					
370Z NISMO	Creep Speed loading and unloading			ONLY B Deck on Tri-level Use 2" Riser		
INFINITI MODELS						
Q50 SEDAN				Use 2" Riser		
Q50 HYBRID				Use 2" Riser		
Q60 COUPE IPL	Creep Speed loading and unloading			No A Deck on Tri-level No C Deck on Rave Door Tri-Levels		CAUTION: Install/remove chock between splashguard and tire
Q60 Convertible				No A deck on Tri-level Must use 2" risers		CAUTION: Install/remove chock between splashguard and tire
Q70 SEDAN				No C deck No A1 or A5 loads * low roof clearance.	Use Power Switch to Fold	A1 & A5 chock to MEDIUM setting behind front wheel
Q70LSEDAN				No C deck No A1 or A5 loads * low roof clearance.	Use Power Switch to Fold	A1 & A5 chock to MEDIUM setting behind front wheel
Q70 SEDAN HYBRID				No C deck No A1 or A5 loads * low roof clearance.	Use Power Switch to Fold	A1 & A5 chock to MEDIUM setting behind front wheel
QX50 CROSSOVER						
QX60 CROSSOVER						Auto Trans in Park
QX70 CROSSOVER						
QX80 SUV					Use Power Switch to Fold	IEC Holden Grate Lock Chock in Max high position